

Growatt Shine4G-X

- Cable free, plug-and-play
- USB communication port
- Built-in memory for up to one month of data
- Online monitoring and maintenance



GROWATT

www.ginverter.com

P O W E R
- I N G O
T O M O -
R R O W O

Datasheet		Shine4G-X
Wireless Parameters		
Wireless type	4G	
System and frequency band	LTE-FDD: B1/B3/B5/B7/B8/B20 LTE-TDD: B38/B40/B41 WCDMA: B1/B5/B8 GSM: 900/1800MHz	
Hardware Parameters		
Data interface	USB	
Operating voltage	5V(±5%)	
Rated power	1.2W	
Display	LED	
Application Parameters		
Supported servers	ShineServer	
Inverter communication	USB (Modbus RTU protocol)	
Server communication	TCP (Modbus TCP protocol)	
Supported network	2G/3G/4G	
SIM card type	Standard SIM card	
Configuration Type	APP Configuration	
Data transmission interval	5 Minutes	
Default server URL	server.growatt.com	
General Data		
Dimensions(L/W/H)	122/47/32mm	
Weight	60g	
Operating temperature	-30°C ~ +65°C	
CE		



SOLSOL s.r.o.
 Technická 3029, 616 00, Brno, ČR
 sales@solsol.cz
 www.solsol.cz